

Liftoverall Insulated




10 - 17 m



Lift Model	VO-29-I	TEL-29-I	TEL-29-EI	VO-32-I	TEL-35-EH	VO-36-I	VST-36-I	VOE-36-MHE	SST-37-EH	ET-36-IFH	VO-40-MHI	SST-40-EH	VST-40-I	VO-42-MHI	VO-43-I	VN-43-I	VST-47-I	VST-5000-I	VO-300-MHI	
Working height	10,90 m	11,10 m	11,30 m	11,80 m	12,75 m	13,00 m	13,10 m	13,30 m	13,30 m	13,00 m	14,10 m	14,20 m	14,30 m	14,90 m	15,00 m	15,30 m	16,30 m	17,10 m	17,30 m	
Platform height	8,90 m	9,10 m	9,30 m	9,80 m	10,75 m	11,00 m	11,10 m	11,30 m	11,30 m	11,00 m	12,10 m	12,2 m	12,30 m	12,90 m	13,00 m	13,30 m	14,30 m	15,10 m	15,30 m	
Max. working outreach	7,00 m	6,70 m	7,40 m	7,0 m	7,00 m	9,55 m	8,50 m	9,30 m	9,00 m	8,00 m	9,90 m	9,0 m	9,70 m	10,70 m	10,90 m	9,20 m	9,90 m	11,70 m	13,40 m	
Max. bucket capacity	181 kg	160 kg	160 kg	160 kg	200 kg	181 kg	272 kg	2X130 kg	200 kg	200 kg	181 kg	200 kg	272 kg	2X160 kg	181 kg	340 kg	227 kg	272 kg	360/2X180 kg	
Max JIB capacity	N/A	N/A	N/A	N/A	N/A	N/A	454 kg	680 kg	N/A	N/A	500 kg	N/A	454 kg	680 kg	N/A	N/A	454 kg	454 kg	907 kg	
Rec. Minimum GVW of the vehicle	5.000 kg	3.500 kg	3.500 kg	5.000 kg	3.500 kg	6.000 kg	7.500 kg	10.000 kg	5.000 kg	4.600 kg	7.500 kg	5.000 kg	7.500 kg	9.000 kg	7.500 kg	10.000 kg	7.500 kg	14.000 kg	15.000 kg	
Minimum GVW of vehicle	C	C	C	C	C	C	C	C	C	V&C	C	C	C	C	C	C	C	C	C	
Note / Options																			Dual buckets	X-MHI available
Max insulation	ANSI Cat. B	ANSI Cat. C	ANSI Cat. C	ANSI Cat. B	ANSI Cat. C	ANSI Cat. B	ANSI Cat. C	ANSI Cat. B	ANSI Cat. C	ANSI CAT. C	ANSI Cat. B	ANSI Cat. C	ANSI Cat. C	ANSI Cat. B	ANSI Cat. B	ANSI Cat. A	ANSI Cat. C	ANSI Cat. B	ANSI Cat. A	



17 - 30 m



Lift Model	VN-50-I	VST-52-I	VO-452-MHI	VST-5500-I	VO-455-I	VO-355-MHI	VO-455-MHE	VN-55-I	VO-360-I	VST-6000-I	VO-360-MHI	VN-60-I	VO-460-MHI	VO-265-I	VO-270-I	VST-7500-I	VST-8000-I	VST-9000-I	VO-I Serie
Working height	17,50 m	17,70 m	18,10 m	18,80 m	18,90 m	18,90 m	19,00 m	19,00 m	18,20 m	18,20 m	18,4 m	18,40 m	20,50 m	22,20 m	23,60 m	24,90 m	26,40 m	29,40 m	29,40 m
Platform height	15,50 m	15,70 m	16,10 m	16,80 m	16,90 m	16,90 m	17,00 m	17,00 m	18,20 m	18,20 m	18,4 m	18,40 m	18,50 m	20,20 m	21,60 m	22,90 m	24,40 m	27,40 m	VST-I Serie
Max. working outreach	10,50 m	9,70 m	14,30 m	12,00 m	14,60 m	14,90 m	15,20 m	11,50 m	15,90 m	12,40 m	16,4 m	16,40 m	16,70 m	14,60 m	15,90 m	14,80 m	15,80 m	17,80 m	VOE-MHI Serie
Max. bucket capacity	340 kg	227 kg	318/2 X 160 kg	272 kg	181 kg	360/2 X 180 kg	318/2 X 160 kg	317 kg	160 kg	272 kg	272 kg	227 kg	227 kg	181 kg	160 kg	360 kg	360 kg	360 kg	VOE-MHI Serie
Max JIB capacity	N/A	454 kg	907 kg	454 kg	N/A	907 kg	907 kg	N/A	N/A	454 kg	907 kg	N/A	907 kg	N/A	N/A	907 kg	454 kg	454 kg	ET-IFH Serie
Rec. Minimum GVW of the vehicle	12.000 kg	9.000 kg	15.000 kg	14.000 kg	12.000 kg	15.000 kg	15.000 kg	12.000 kg	12.000 kg	14.000 kg	15.000 kg	14.000 kg	15.000 kg	15.000 kg	15.000 kg	15.000 kg	15.000 kg	18.000 kg	VO-MHI Serie
Minimum GVW of vehicle	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	VST-I Serie
Note / Options				Dual buckets		X-MHI				Dual buckets	X-MHI								VST-I Serie
Max insulation	ANSI Cat. A	ANSI Cat. C	ANSI Cat. A	ANSI Cat. B	ANSI Cat. B	ANSI Cat. A	ANSI Cat. A	ANSI Cat. A	ANSI Cat. B	ANSI Cat. B	ANSI Cat. A	ANSI Cat. A	ANSI Cat. A	ANSI Cat. B	ANSI Cat. B	ANSI Cat. A	ANSI Cat. A	ANSI Cat. A	VO-MHI Serie
																			VN-I Serie

Color Codes: